

Twin CORE X5



Flexible Communications Platform

The Twin CORE X5 is a compact, rugged communications hub designed for a diverse range of applications. This durable device integrates bonded multi-channel cellular 5G LTE, Wi-Fi, GPS, and optional Land Mobile Radio extension capabilities. It can be mounted in vehicles, installed in a rugged carry case (CORE CommsKit), or utilized in stationary facilities. Engineered for ease of use with leading-edge technology, the Twin CORE X5 is prepared to address your evolving communication requirements.

The Basics

- Compact and rugged design enables diverse deployment solutions
- DC power / AC power (optional)
- No moving parts affected by vehicle movement
- 2x 5G channels with LTE fallback/2 SIM slots per Twin CORE
- A large, secure Wi-Fi coverage area for body cameras, healthcare monitoring devices, and other wireless systems
- Integrated GPS tracking
- Interconnect points for data units, biometric equipment, and other wired devices
- Suitable for single deployments or large enterprises

Scalability and Operations

- Two 5G radios onboard with LTE fallback.
- The remote management server, NetView series, monitors, configures, and checks in on all CORE systems, reducing maintenance and downtime while providing integrated system status reports.
- Twin CORE X5 systems automatically register with the optional NetView series server when turned on and are visible on the network for the entire duration.
- Powerful and secure Wi-Fi with a large effective range, securing authorized devices. Wi-Fi mesh is possible with multiple Mobile CORE systems deployed within a given territory.




Every Twin CORE X5 has sophisticated software that manages cell tower handoffs as you travel, maximizing signal strength and automatically searching for the best throughput connection available. Use of bonded aggregation allows Twin CORE users the ability to maintain session persistence even if one or more of the cell connections fail for any reason. The optional LMR extension functions in the background to detect loss of service to the trunked radio network and will send the transmission over the 5G connection. This requires no action by the operator.

Twin CORE X5

Product Specification Data Sheet

Billet milled aluminum case for mobile, portable and office applications



Our devices automatically search for the best throughput connection available. If all 5G and LTE connections are lost, Mobile CORE will automatically connect to the satellite. If the device finds an available cellular connection it will reconnect to that service, hands-free. The customer does not have to monitor AGILE Routing.

Products: Twin CORE X5, Systems: Twin Core CommsKit X5			
Data Rates per 5G Channel, 2 Channels	5G SA Sub-6: Download 2.4 Gbps; Upload 900 Mbps 5G NSA Sub-6: Download 3.4 Gbps; Upload 550 Mbps	WLAN Security	WPA, WPA 2, WPA-PSK, WPA-EAP
Global 5G FR1 Bands Supported	- NSA: n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 29/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 75/ 76/ 77/ 78/ 79 - SA: n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 29/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 75/ 76/ 77/ 78/ 79	Wired	4 2.5 Gigabit LAN/WAN configurable RJ-45 Ethernet Ports 1 RJ-45 Port can be POE 1 USB 3.2 Ports
Data Rates per LTE Channel, 2 Channels (LTE Cat 19 Download, Cat 18 Upload)	Download 2.4 Gbps; Upload 900 Mbps	GPS	Active NMEA Passive NEMA
Global: (Worldwide LTE) Bands Supported	- LTE-FDD: B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 13/ 14/ 17/ 18/ 19/ 20/ 25/ 26/ 28/ 29/ 30/ 32/ 66/ 71 - LTE-TDD: B34/ 38/ 39/ 40/ 41/ 42/ 43/ 48 - LTE-LAA: B46	Processing	Raspberry Pi 5, 64-bit quad-core Arm Cortex-A76 processor running at 2.4GHz
Data Rates per WCDMA Channel, 2 Channels	Download 42 Mbps; Upload 5.76 Mbps	Structure Power	4 to 40 VDC
Global: UMTS Bands Supported	WCDMA B1/ 2/ 4/ 5/ 8/ 19	Security FIPS-140-2	Optional
2 3FF Micro SIM slots		Weight	1.2lbs / 547kg
Twin CORE X5	6 GSM antennas the unit has 2 internally mounted Wi-Fi antennas.	Operating Range	-22°F to 167°F / 30°C to +75°C - IP64 rated
AGILE LTE antennas:	- Antenna Standard - SMA connected antenna low height directional - Antenna Premium - SMA connected antenna mid height directional - Antenna Premium - Wired SMA lead antenna flat panel	Dimensions	7.3622 in (L) x 4.68504 in (W) x 2.83465 in (H) 187 mm (L) x 119 mm (W) x 72 mm (H) 7.3622 in (L) x 6.41732 in (W) with mounting brackets x 2.83465 in (H) 187 mm (L) x 163 mm (W) with mounting brackets x 72 mm (H)
WAN protocol for cellular/satellite/other WAN connected interfaces.		VPN	IPSEC Tunneling
Wi-Fi	- Dual Band 2.4/5 GHz 802.11a/b/c/g/n/ac	Warranty and Service Standard	1 Year Limited Hardware 1 Year standard or premium support available 1 year support and hardware warranty extensions are available for years 2 through 5



WE ARE AGILE

We engineer the hardware. We design the software.
We build the solution. With committed support